



蓝畅科技
BLOVEDREAM



T80

INTERNET OF THINGS HANDHELD TERMINAL

4.5-inch HD screen · Quad -core

4G full Netcom



Android



4G



WIFI



Bluetooth



1D barcode



2D barcode



NFC



Camera



GPS



Product parameters

Performance

Quad core	
CPU	Cortex-A53 Quad-core 64-bit 2.0GHz high-performance processor
RAM+ROM	2GB+16GB Supports up to 3GB+32GB
Expand memory	Micro SD(TF) Supports up to 128GB
System	Android 8.1/Android9.0

Data communication

WLAN	Dual-band 2.4GHz / 5GHz, Supporting IEEE 802 a/b/g/n/ac protocol
WWAN	2G: GSM (850/900/1800/1900MHz)
	3G: WCDMA (850/900/1900/2100MHz)
	4G: FDD:B1/B3/B4/B7/B8/B12/B20 TDD:B38/B39/B40/B41
Bluetooth	Support Bluetooth 5.0+BLE Transmission distance 5-10 meters
GNSS	Support GPS, Galileo, Glonass, Beidou

Physical parameter

Dimensions	166mm×77.5mm×22mm
Weight	<500g
Display	4.5 inch IPS color display with resolution 480*854
TP	Corning Gorilla glass, supports multi-touch
Battery capacity	rechargeable polymer battery (3.8V 4200mah) removable
	Standby time >350 hours
	Working time > 12 hours
	Charging time <4H, using standard power adapter and data cable
Expansion Card slot	Micro SIM card x 1 , TF card × 1
Communication interface	Type-C USB x 1, OTG,POGO Pin x 1
Audio	Speaker (mono), Microphone, Receiver
Keypad	Support touch screen soft keypad and physical keypad
Sensor	Gravity Sensor,Vibration motor

Language/input method

Input	English, Pinyin, Five strokes, Handwriting input, Support soft keypad
Language	Language packs in Simplified Chinese, Traditional Chinese, English, Korean, Japanese, Malaysian, etc.

Data collection

Barcode scanning (Optional)	
1D Scanning engine	Mindeo SE966 ,Honeywell N4313
1D Symbolologies	Code128,EAN-13,EAN-8,Code39,UPC-A,UPC-E,Codabar,Interleaved 2 of 5,China post 25,ISBN/ISSN, Code93,UCC/EAN-128, GS1 Databar,HIBC, etc.
2D Scanning engine	Newland E483 ,Honeywell N5703 N6603 N6601
2D Symbolologies	PDF417,Micro PDF417,GS1 Composite,Aztec Code,Data Matrix,QR Code,Micro QR Code, MaxiCode,Hanxin Code, etc.

Camera (Standard)

Rear camera	8MP HD camera,Support auto focus, Flash, Anti-shake, Macro shooting
-------------	---

NFC (Optional)

Frequency	13.56MHz
Protocol	Support ISO14443A/B, 15693 agreement
Distance	2cm-5cm

User environment

Operating temperature	-20℃ - 55℃
Storage temperature	-40℃ - 70℃
Environment humidity	5%RH--95%RH(no condensation)
Drop specification	6 sides Supports 1.5 meters drops on the marble within the operating temperature
Rolling test	0.5m rolling for 6 sides, can still work steadily
Protection level	IP66

Accessories

Standard	Adapter, Data cable, Protective film, Instruction manual
----------	--

Special Note: Product data is for reference only and subject to change without notice.

model: T80

Update : 2022-03-10



Company : Blovedream Technology Co., Ltd.

Official website: www.lckj.cn | www.blovedream.net

National hotline: 0755-26072520

Address: 4th Floor, Building A, Phoenix Zhigu Building, Country Garden, Xixiang, Baoan District, Shenzhen