

T80U

INTERNET OF THINGS HANDHELD TERMINAL

4.5-inch HD screen · Octa-Core · 4G full Netcom







4G







Bluetooth 1D barcode















GPS













Product Specifications

Performance	
Octa Core	
CPU	MT6765 Octa-core 64-bit 2.3GHz high performance processor
RAM+ROM	4GB+64GB
Expand memory	Micro SD(TF) Supports up to 128GB
System	Android 13.0

Expand momory	mioro ob(11) oupporto up to 1200b	
System	Android 13.0	
Data Communication		
WLAN	Dual-band 2.4GHz / 5GHz, support IEEE 802.11ac/a/b/g/n/d/e/h/i/j/k/r/v protocol	
WWAN	2G: GSM (850/900/1800/1900MHz)	
	3G: WCDMA (850/900/1900/2100MHz)	
	4G: FDD:B1/B3/B4/B7/B8/B12/B20 TDD:B38/B39/B40/B41	
Bluetooth	Support Bluetooth 5.0+BLE Transmission distance 5-10 meters	
GNSS	Support GPS, Galileo, Glonass, Beidou	

Physical Specifications		
Dimensions	166mm×77.5mm×22mm	
Weight	<500g	
Display	4.5 inch IPS color display with resolution 480*854	
Screen brightness	>500cd/m2	
TP	Support multi-touch	
Battery capacity	rechargeable polymer battery (3.8V 4330mAh) removable	
	Standby time >350 hours	
	Charging time <4H, using standard power adapter and data cable	
Expansion Card slot	Micro SIM card x 1 , TF card × 1	
Communication interface	Type-C USB x 1, OTG,POGO Pin x 1	
Speaker volume	>80db (test distance 10cm)	
Audio	Speaker (mono), Microphone, Receiver	
Keypad	Support touch screen soft keypad and physical keypad	

Language/Input Method		
Input	English, Pinyin, Five strokes, Handwriting input, Support soft keypad	
Language	Language packs in Simplified Chinese, Traditional Chinese, English, Korean, Japanese, Malaysian, etc.	

Gravity Sensor, Vibration motor

Data Collection		
Barcode Scanning (Optional)	
1D Scanning engine	Mindeo966 ,Honeywell N4313	
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS,etc. Postal Codes:USPS Planet, USPS Postnet, China Post, Korea Post, Australian Postal, Japan Postal, Dutch Postal (KIX), Royal Mail, Canadian Customs, etc	
2D Scanning engine	E483 ,Honeywell N5703 N6703 N6703HD, N6602-W2	
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, HanXi,etc.	
Camera (Standard)		
Rear camera	8MP HD camera, Support auto focus, Flash, Anti-shake, Macro shooting	
NFC (Optional)		
Frequency	13.56MHz	
Protocol	Support ISO14443A/B, 15693 agreement	
Distance	2cm-5cm	
User Environment		
Operating temperature	-20℃ - 55℃	
Storage temperature	-40℃ - 70℃	
Environment humidity	5%RH95%RH(no condensation)	
Drop specification	6 sides Supports 1.5 meters drops on the marble within the operating temperature	
Rolling test	0.5m rolling for 6 sides, can still work steadily	
Protection level	IP66	
Accessories		
Standard	Adapter, Data cable, Protective film, Instruction manual	

Special Note: Product data is for reference only and subject to change without notice. model: T80 Update: 2025-7-7



Sensor